

摄控一体摄像机

4K POV 摄像机**BC-15P**

视频格式	2160p 60/59.94/50/30/29.97/25 1080p 60/59.94/50/30/29.97/25
感光元件	1/2.3英寸 CMOS
有效像素	12.3Mega Pixels
信噪比	50 dB
最低照度	0.5Lux (F1.0, AGC ON)
电子快门	1/25(1/30), 1/50(1/60), 1/75(1/90), 1/100(1/120), 1/125(1/150), 1/150(1/180), 1/200(1/210), 1/500(1/600), 1/1000(1/1200), 1/2000(1/2400), 1/4000(1/4800), 1/8000(1/9000) sec
镜头	2x Digital Zoom
伽马设定	Standard / Mode1 / Mode2 / Mode3
光圈设定	Fixed IRIS (F1.0)
数字降噪	2D/3D
选单语言	English/Simplified Chinese/Traditional Chinese
白平衡	Auto, Indoor, Outdoor, OnePush, Color Temp., R/B Gain, Lock
AGC/增益控制	Auto□AGC□/ Manual / Lock□Follow Exposure Mode□
镜头翻转	Yes
对焦模式	Full Manual
焦距	Standard Lens: 6mm Wide Lens: 2.8mm
视角	Standard Lens: H: 38.6, V:21.9, D: 44.1 Wide Lens: H: 75.5, V:46.6, D:82.7
图像补偿	Auto
视频输出接口	HDMI 2.0 x1 RJ45 x1
音频输入接口	3.5mm Line in/Mic in (Stereo)
TALLY灯	Dual color (Red, Green)
滤片或广角镜	IR cut built-in
控制协议	DVIP
远程控制接口	RJ-45: for IP control (DVIP)
视频压缩格式	H.264, H.265, Dual stream output
音频压缩格式	AAC
音频比特率	128Kbps
高清IP接口	10/100/1000M
串流协议	TS over TCP/UDP, RTMP(S), HLS, SRT

第一串流直播分辨率	1920x1080 1280x720 1024x576 960x540 640x480 640x360
第二串流直播分辨率	1920x1080 1280x720 1024x576 960x540 640x480 640x360
视频比特率	1Mbps ~ 7Mbps (Single Stream) 1Mbps ~ 7Mbps (Copy Stream) 1Mbps ~ 4Mbps (Dual Stream)
视频比特率模式	VBR, CBR
编码帧率	50Hz: 1-25fps 60Hz: 1-30fps
POE模块	IEEE802.3af
固件更新	Ethernet
摄像机控制器	RMC-300 series/PTZ View Assist APP
脚架用螺丝尺寸	1/4-20 UNC
颜色	Black
尺寸	77mm (W) x 82mm (D) x 78mm (H)
重量	200 g
操作温度	0~40 °C
电源	DC 12V 9W
包装明细	1 x BC-15P Main Unit 1 x Standard Lens (attached on camera with lens cap) 1 x Wide-angle Lens (attached with lens caps) 1 x DC 12V power adaptor