

视频格式转换器

4K 多格式视频转换器**DAC-45****Configuration**

转换功能	VGA/HDMI/SDI to 4K HDMI/3G-SDI Multi-format Up/Down/Cross
视频输入	1x VGA, 1x HDMI, 1x HD/SD-SDI 1x Reference Input
回路输出	----
视频输出	1x SDI, 1x HDMI
音频输入	2x RCA(Unbalanced Audio L/R), 2x SDI/HDMI Audio embedded
音频输出	SDI embedded audio up to 8CH, 48KHz, PCM audio HDMI embedded audio up to 8CH, 48KHz, PCM audio
音频格式选择	----
音频增益	----
视频格式	2160p(23.98/24/25/29.97/30/50/59.94/60Hz), 1080p(23.98/24/25/29.97/30/50/59.94/60Hz), 1080psf(23.98/24/25/29.97/30Hz), 1080i (50/59.94/60Hz), 720p (50/59.94/60Hz), 625i, 576p, 576i, 525i, 480p, 480i, 1920x1080(60Hz), 1280x720(60Hz), 1600x1200(60Hz), 1400x1050(60Hz), 1366x768(60Hz), 1280x1024(60Hz), 1024x768(60Hz), 800x600 (60Hz)
输出分辨率	2160p(23.98/24/25/29.97/30/50/59.94/60Hz), 1080p(23.98/24/25/29.97/30/50/59.94/60Hz), 1080psf(23.98/24/25/29.97/30Hz), 1080i (50/59.94/60Hz), 720p (50/59.94/60Hz), 625i, 576p, 576i, 525i, 480p, 480i
均衡器	Yes
重新锁定	Yes
SDI电缆驱动器	Yes
固件更新	Mini USB x 1
尺寸	220 x 143 x 42 mm
重量	1 kg
操作温度	0~40 °C
电源	DC 12V, 9.4W
包装明细	1 x DAC-45 1 x AD Switch DC 12V