

网络直播编码器

双平台网络直播编码器**NVS-35**

视频输入	HDMI x1 SDI x1
支持视频格式	1080p 60/59.94/50 1080p 30/29.97/25/24/23.98 1080i 60/59.94/50 720p 60/59.94/50 480i 59.94, 576i 50
视频输出	Support Down Scaling to 128x128
音频输入	1 x HDMI embedded audio (Audio depends on the source/ both stereo and mono supported) 1 x SDI embedded audio 1 x RCA (audio level calibration: +10/+12dB ~ -6dB) 2 x XLR (audio level calibration: +10/+12dB ~ -6dB) Mix (Embedded + RCA+XLR)
编码格式	H.264/AVC High Profile Level 4.1
视频码流	Record Only: Up to 16Mbps (1080p50/60) Stream Only: Up to 10Mbps (1080p50/60) Rec and Stream: Up to 36Mbps (1080p50/60) (dual stream)
音频模式	Stereo/Mono
音频码流	AAC-LC Sample rate: 48KHz, 16bit Configurable bit rate: 128K or 256K or 384K
音频延迟	Delay time: 0-3000ms
串流协议	TS over TCP/UDP (unicast & multicast) RTSP over HTTP/TCP/UDP (RTSP Elementary Stream) RTMP/RTMPS(Publish) SRT
网络接口	1x RJ45 (10/100Mbps Ethernet)
录像文件格式	MP4, TS
存储方式	SD Card x1 (File System: NTFS, FAT, exFAT)
特殊功能	Vertical video stream(rotate & crop)
电源	DC 12V 12W
尺寸	220 x 95 x 47 mm
重量	0.78 kg
操作温度	0~40 °C
包装明细	1 x NVS-35 product 1 x AD Switch DC 12V