

液晶监视器

17.3英寸 4K 液晶监视器-1U机架式**TLM-170FM**

面板	17.3英寸 LED Backlit
外观	1U机架抽拉式
分辨率	1920x1080
可视角度	(H) +89/-89° (V) +89/-89°
亮度/对比	300cd/m ² 700:1
视频输入	1 x 12G SDI 2 x HDMI (2.0)
环通输出	1 x 12G SDI 1 x HDMI (2.0)
支持视频格式	SDI: 4096x2160p (23.98/24/25/29.97/30/50/59.94/60) 3840x2160p (23.98/24/25/29.97/30/50/59.94/60) 4096x2160Psf (23.98/24/25/29.97/30) 3840x2160Psf (23.98/24/25/29.97/30) 1920x1080p (23.98/24/25/29.97/30/50/59.94/60) 1920x1080i (50/59.94/60) 1920x1080Psf (23.98/24/25/29.97/30) 1280x720p (23.98/24/25/29.97/30/50/59.94/60) 525i, 625i HDMI: 4096x2160p (23.98/24/25/29.97/30/50/59.94/60) 3840x2160p (23.98/24/25/29.97/30/50/59.94/60) 1920x1080p (23.98/24/25/29.97/30/50/59.94/60) 1920x1080i (50/59.94/60) 1280x720p (23.98/24/25/29.97/30/50/59.94/60) 720 x480i (NTSC), 720 x576i (PAL) 640 x800, 800 x600, 1024 x768, 1280 x800
长宽比显示模式	16:9, 4:3
比例标记	YES
安全标记	YES
Tally模式	Live (Red) Cued (Green)
音频输入/输出	Input: Embedded Audio (48KHz sampling) Output: Analog stereo (Phone Jack) Speaker x 2 (3W)

特别功能	waveform, vector scope, Focus Peaking, False Color, Exposure (Zebras), Histogram, HDR / SDR, Time Code, Audio Vector, Camera Log, Gamma, Marker, Pixel to Pixel, Zoom, H/V Delay, DSLR, Freeze, Image Flip, Check Field, Level Meter, Color Bar, Color Calibration.
尺寸	403 x 305 x 37 mm
重量	4.7kg
操作温度	0~40 °C
电源	DC 12V, 34.6W
包装明细	1 x TLM-170FM product 1 x AD Switch DC 12V 1 x Monitor Stand 2 x Velcro