

液晶监视器

17.3英寸 4K 液晶监视器-7U机架式**TLM-170FR**

| | |
|---------|---|
| 面板 | 17.3英寸 LED Backlit |
| 外观 | 7RU Rack Mount |
| 分辨率 | 1920x1080 |
| 可视角度 | (H) +89/-89° (V) +89/-89° |
| 亮度/对比 | 300cd/m ² 700:1 |
| 视频输入 | 1 x 12G SDI 2 x HDMI (2.0) |
| 环通输出 | 1 x 12G SDI 1 x HDMI (2.0) |
| 支持视频格式 | SDI: 4096x2160p (23.98/24/25/29.97/30/50/59.94/60) 3840x2160p (23.98/24/25/29.97/30/50/59.94/60) 4096x2160Psf (23.98/24/25/29.97/30) 3840x2160Psf (23.98/24/25/29.97/30) 1920x1080p (23.98/24/25/29.97/30/50/59.94/60) 1920x1080i (50/59.94/60) 1920x1080Psf (23.98/24/25/29.97/30) 1280x720p (23.98/24/25/29.97/30/50/59.94/60) 525i, 625i HDMI: 4096x2160p (23.98/24/25/29.97/30/50/59.94/60) 3840x2160p (23.98/24/25/29.97/30/50/59.94/60) 1920x1080p (23.98/24/25/29.97/30/50/59.94/60) 1920x1080i (50/59.94/60) 1280x720p (23.98/24/25/29.97/30/50/59.94/60) 720 x480i (NTSC), 720 x576i (PAL) 640 x800, 800 x600, 1024 x768, 1280 x800 |
| 长宽比显示模式 | 16:9, 4:3 |
| 比例标记 | YES |
| 安全标记 | YES |
| Tally模式 | Live (Red) Cued (Green) |
| 音频输入/输出 | Input: Embedded Audio (48KHz sampling) Output: Analog stereo (Phone Jack) Speaker x 2 (3W) |

| | |
|------|---|
| 特别功能 | waveform, vector scope, Focus Peaking, False Color, Exposure (Zebras), Histogram, HDR / SDR, Time Code, Audio Vector, Camera Log, Gamma, Marker, Pixel to Pixel, Zoom, H/V Delay, DSLR, Freeze, Image Flip, Check Field, Level Meter, Color Bar, Color Calibration. |
| 尺寸 | 403 x 305 x 37 mm |
| 重量 | 4.7kg |
| 操作温度 | 0~40 °C |
| 电源 | DC 12V, 34.6W |
| 包装明细 | 1 x TLM-170FR product 1 x AD Switch DC 12V 1 x Monitor Stand 2 x Velcro |